

NAK



KTA3601(KTA DIN 25414,

•

- 0.0028 (l/s)/m² 0.01 (m³/h)/m² 2000 Pa
-
-
-
-
- 5000Pa
-

-
-
-
- 3 × 230 V AC (400 V AC) 230 V AC

- NAK
- KTA3601 KTA DIN25414

-
-
- 0.0028 (l/s)/m² 0.01 (m³/h)/m² 2000Pa
- 5000Pa

- NAK-H:
- NAK-P:
- NAK-E: (400 V AC, 50 Hz)
- NAK-E1: (230 V AC, 50 Hz)

-
- G:

-

- U 3mm
- 2mm
-
-
-
-

- EN 10142-DX51D+Z150-200
- EN 10327-DX51D+Z150-200-NAC
-
-
- 80°C
- RAL7001

30

2

KTA 3601 KTA DIN 25414

5000Pa

-
-
- 0.0028 (l/s)/m² 0.01 (m³/h)/m² 2000Pa
- 5000Pa

- EN 10142-DX51D+Z150-200
- EN 10327-DX51D+Z150-200-NAC
-
-
- 80°C
- RAL7001

-
- G:

- : 400 × 270 1000 × 1000 mm
- 5000 Pa,
- : < 0.0028 (l/s)/m² 0.01 (m³/h)/m²

NAK – P – G – R / 800×755 / Z05



NAK		R
		L
H		mm
P		B × H
E	400 V	
E1	230 V	
		:
		Z01 – Z07
G		:



46
215021
:(+86) 0512-67168869

>
: (+86) 021-52981838
: troxchn@troxchina.com

>
: (+86) 010-88016761
: troxbj@troxchina.com

: (+86) 020-34072475
: troxgz@troxchina.com

TROX

