



FS

FS - 304/316L - 304/316L

FS - 304/316L - 304/316L

- 304/316L - 304/316L
- 304/316L - 304/316L
- G $\frac{1}{2}$ " - G $\frac{3}{4}$ "
- 90°
- 500, 750, 1000 mm
- 304/316L

FS - 304/316L

- Ø12 mm 90°
- G $\frac{1}{2}$ " 90°
- G $\frac{1}{2}$ " 90°

□□□□□□□□□□□□□□□□□□□□□□

□□

- □□□□□□□□
- □□□□□□□□□□□□□□

□□□□□

- □□□□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□□□□□

□□

- □□□□□□□□□□
- Ø10 mm □□□□□□□□□□□□□□□□□□□□

□□□□□

- □□□□ 500, 750, 1000 mm
- □□□□: 10 □□ 13 mm, □□□□□□□□ □□ □□□□ □□□□ □□□□
- □□□□□□□□□□ 6 bar
- □□□□□□ □□ -20 °C □□ +55 °C

FS



[1] Accessories

FS Connecting hoses

[2] Nominal size [mm]

10
13

[4] Connection type 2

[5] Nominal size [mm]
500
750
1000

[3] Connection type 1

SG10 Push-fit coupling, straight, Ø10 mm
(NW 10 only)

SG12 Push-fit coupling, straight, Ø12 mm

SW10 Push-fit coupling, 90°, Ø10 mm (NW 10 only)

SW12 Push-fit coupling, 90°, Ø12 mm

A1/2 G½" external thread with flat seal

U1/2 G½" union nut with flat seal

UW1/290° G½" union nut with flat seal