

- 60% 45%
-

- WG:
- WG-A2:
- WG-AL:
- WG-B-AL:

-

2-2.5m/s

ISO 7235

-
-
-
- 60% 45%
-

- 200×165-2400×1650/1600×2310
- 4900mm
- 4720mm
- WG-B-AL 165-1980mm
- 40-13350l/s 144-48660m³/h 2.5m/s
- 60% 45%
- 30Pa 2.5m/s
- 35Pa 2.5m/s

WG - AL - 2 - / 600x1155 / ER / P1 - RAL ...



WG 600x1155

600x1155
B x H
(B x H > 4 m² 600x1155)

A2 600x1155
AL 600x1155

ER 600x1155
600x1155 (600x1155U)

1 600x1155, 600x1155!
600x1155, 600x1155 (600WG, WG-AL)
2 600x1155, 600x1155 (600WG-AL)
3 600x1155, 600x1155 (600WG-AL, WG-A2)
U 600x1155
1, 2, 3 600x1155 U600x1155

P1 600x1155 RAL CLASSIC
PS 600x1155, DB600x1155

S2 600x1155WG-AL
600x1155EURAS600x1155, E6-C-31...35600x1155600x1155
S3 600x1155EURAS600x1155E6-C-0600x1155600x1155

600x1155:
RAL 9010 50 %
RAL 9006 30 %
600x1155RAL colours 70 %