



CAK



CAK

CAK

- RAL TRGS 905 EU 97/69/EG
- 20m/s
- DIN 4102 B1 PP
- DIN8077 DIN8078
- ISO7235
- EN15727 D

•



- CAK
- TVRK TVLK

- ISO7235



- CAK
- VF2

- ①

- GZ

- DIN8077 DIN8078
- 1000Pa
- 10 100°C

- DIN 4102 B1 PP
-

- EN13501 A2
- RAL RAL-GZ 388
- TRGS 905 EU 97/69/EG
- 20m/s
-

ISO7235

RAL RAL-GZ388

DIN8077

EN15727 D

- ISO7235
-

- DIN 4102 B1 PP
-

- EN13501 A2
- RAL RAL-GZ 388
- TRGS 905 EU 97/69/EG
- 20m/s
-

- 125 to 400 mm
- 1000Pa
- 100°C

CAK / 160x1000 / GZ / VF2



CAK	4 [mm]	500
		1000
		1500
3 [mm]		
125		
160		
200	5	
250		
315	GZ	(VF2)
400		
	VF2	



>

>

: (+86) 021-52981838
: troxchn@troxchina.com

: (+86) 010-88016761
: troxbj@troxchina.com

: (+86) 020-34072475
: troxgz@troxchina.com



32059002005016

46
215021
: (+86) 0512-67168869